


2711 PROFILE

Floor Recessed Series



DIMENSIONS



A RAISED FLOOR LIGHT WITH EASE IN MIND

Meant to be easily embedded in the floor, this light is sturdy with a raised and beveled trim around its face.

FEATURES

- Compatible with LED engines up to 12mm wide.
- The opaque lens provides uniform light without hot spots.
- Custom length by sections of 2 to 196 inches.
- Constructed from high-grade 6063-T5 aluminum alloy for heat dissipation.
- This optimal heat dissipation maximizes the lifespan of the LEDs.
- The PMMA lens has high transmittance and resistance to discoloration.
- Designed to meet North-American woodworking standards.











2711 PROFILE ORDERING SHEET

| PROFILE | LENS | LENGTH | LIGHT | USAGE | DRIVER | MOUNT |
|---|--|--|--|---|---|--|
|  ▶ 2711 - Silver |  O - Opaque Lens |  Custom length in segments of 2 to 196 inches. | 760lm 5.5W/ft  ▶ 27 - 2700K  ▶ 30 - 3000K  ▶ 40 - 4000K  ▶ 50 - 5000K  ▶ 60 - 6000K 365lm 4.3W/ft  ▶ CCT - 2700-6500K  RGB - RGB |  ▶ IP20 - Dry Areas  ▶ IP68 - Wet Areas Single CCT: 370lm 4.4W/ft |  ▶ 30W AC120-277V  ▶ 60W AC120-277V  ▶ 96W AC120-277V 5-in-1 dimming TRIAC, 0-10V, 1-10V, PWM, Potentiometer |  ▶ D - Mounting Clip |
|  RAL N2 - Any Color Custom powder coating |  ▶ F - Frosted Lens  C - Clear Lens | | | | | |
| PROFILE | LENS | LENGTH | LIGHT | USAGE | DRIVER | MOUNT |

Mark "N/A" to signify options you do not need.

ITEM CODES

- | | |
|---|---|
|  12510 - Linear Extrusion |  40662-A - 30W Driver |
|  12510-A - End Caps |  40662-B - 60W Driver |
|  12510-B - Frosted Lens |  40662-C - 96W Driver |
|  40662-F - CCT Remote |  12510-C - Mounting Clip |

Draw your dream fixture below and let us make it a reality.

