

| Project: | Туре: |
|----------|-------|
|----------|-------|

Name:_____ Date:____







| Size | 13.8" W x 8.8" H x 4.6" D 17.8" W x 12.7" H x 4.6"D |
|---------------|--|
| Watts | 60W, 120W |
| Voltage | 120-277V |
| Dimming | 0-10V |
| Beam Angle | 110° |
| CRI | >80 |
| PF | ≥ 0.9 |

| Lumens | 7,800-8,400lm 15,600-16,800lm | |
|-----------|----------------------------------|--|
| ССТ | 3000K-4000K- 5000K | |
| IP Rating | IP65 | |
| Materials | Aluminum, Glass | |
| Finish | Bronze | |
| Lens | Clear | |
| Lifespan | 50,000 Hours | |

SARIN LED CCT SLIM WALL PACKS light up your outdoor spaces in rain, snow and darkness with bright and high quality LEDs. These wall packs are built to run for long periods and save you money through energy efficiency and far fewer replacement intervals. These fixtures also feature a photocell light sensor that automatically switches the unit on or off depending on the amount of light it detects.

This wall pack adopts the latest technology, replacing traditional bulbs with energy efficient LEDs. These are widely used in the lighting of homes, hotels, garages, streets, landscapes and other commercial spaces. Wall Pack lights are popular in entryways, for general area lighting, perimeter lighting, and storage facilities. These fixtures are suitable for a variety of applications and will provide significant energy savings.

OVERVIEW

CCT: Tunable

Applications: Indoor Outdoor (IP)

Efficacy: 125-135lm/W

Dimming: 0-10V

LED Type: SMD 2835

Lens Type: Clear

Driver: BQE120C-130-PVF-Z

Operating Temp: $-40F^{\circ}$ to $113F^{\circ}$

Operating Humidity: 20% - 90% RH

Lifespan: 50,000 Hours


Warranty: 5 Years

FEATURES

- Photocell Light Sensor automatically activates the lights when dark
- Bright and uniform, instant start, non-flickering, nonhumming LEDs










| Project: | Туре: |
|----------|-------|
| • | |

DIMENSIONS:


60W:









120W:









| Project: | Type: | | |
|----------|-------|--|--|
| | | | |
| Name: | Date: | | |

ORDER FORM:

| | | | (*) Spec | ial Order/Not Com | nmonly Stocked |
|--|----------------------------------|----------------------|---------------------------|----------------------|--------------------------|
| Custom Model Assembly | | | | | |
| SES-SWP09-CCT-60W Example Model Number | Fixture √ SWP09 | CCT ✓ Tunable | Watts ☐ 60W ☐ 120W | Beam Angle ✓ 110° | Voltage 120-277 √ |
| SES | - SWP09 | — Tunable | _ | – 110° | – 120-277V |
| Quantity | Fivtura | CCT | \Matte | Beam Angle | Voltage |

Common Stock Models:

| Item # | Model # |
|--------|--------------------|
| 11338 | SES-SWP09-CCT-60W |
| 11339 | SES-SWP09-CCT-120W |